

| BOGE Type | Max. pressure | | Effective free air delivery* | | Motor power | | Dimensions silenced | Dimensions super-silenced | Compressed air outlet | Weight silenced kg | Weight super-silenced kg |
|------------|---------------|------|------------------------------|------|-------------|----|---------------------|---------------------------|-----------------------|--------------------|--------------------------|
| | bar | psig | m ³ /min | cfm | kW | HP | W x D x H (mm) | W x D x H (mm) | | | |
| CLF 9 | 8 | 115 | 0.26-1.27 | 9-45 | 7.5 | 10 | 1020 x 532 x 723 | 1020 x 532 x 796 | G 1/2 | 200 | 208 |
| CLF 9 | 10 | 150 | 0.25-1.12 | 9-40 | 7.5 | 10 | 1020 x 532 x 723 | 1020 x 532 x 796 | G 1/2 | 200 | 208 |
| CLF 9 | 13 | 190 | 0.24-0.93 | 8-33 | 7.5 | 10 | 1020 x 532 x 723 | 1020 x 532 x 796 | G 1/2 | 200 | 208 |
| CLF 9-270 | 8 | 115 | 0.26-1.27 | 9-45 | 7.5 | 10 | 1820 x 633 x 1270 | 1820 x 633 x 1343 | G 1/2 | 315 | 323 |
| CLF 9-270 | 10 | 150 | 0.25-1.12 | 9-40 | 7.5 | 10 | 1820 x 633 x 1270 | 1820 x 633 x 1343 | G 1/2 | 315 | 323 |
| CLF 9-250 | 13 | 190 | 0.24-0.93 | 8-33 | 7.5 | 10 | 1620 x 633 x 1270 | 1620 x 633 x 1343 | G 1/2 | 310 | 318 |
| CLDF 9-270 | 8 | 115 | 0.26-1.27 | 9-45 | 7.5 | 10 | 1820 x 633 x 1270 | 1820 x 633 x 1343 | G 1/2 | 362 | 370 |
| CLDF 9-270 | 10 | 150 | 0.25-1.12 | 9-40 | 7.5 | 10 | 1820 x 633 x 1270 | 1820 x 633 x 1343 | G 1/2 | 362 | 370 |
| CLDF 9-250 | 13 | 190 | 0.24-0.93 | 8-33 | 7.5 | 10 | 1620 x 633 x 1270 | 1620 x 633 x 1343 | G 1/2 | 357 | 365 |

*Free air delivery for complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.
 Further sizes of receiver on demand.
 Emitted sound pressure level as per PN8NTC2.3 from **70 dB(A)**.