

CL series compressor unit

| BOGE Type | Max. pressure | | Free air delivery* | | Free air delivery* | | Motor power | | Dimensions in mm W x D x H | Weight kg |
|-----------|---------------|------|--------------------|-----|--------------------|-----|-------------|-----|-------------------------------|-----------|
| | bar | psig | 50 Hz m³/min | cfm | 60 Hz m³/min | cfm | kW | HP | | |
| CL 3 | 10 | 150 | 0.240 | 9 | – | – | 2.2 | 3 | 755 x 485 x 495 | 105 |
| CL 4 | 10 | 150 | 0.340 | 12 | 0.310 | 11 | 3 | 4 | 755 x 485 x 495 | 110 |
| CL 4 | 13 | 190 | 0.234 | 8 | – | – | 3 | 4 | 755 x 485 x 495 | 110 |
| CL 5 | 10 | 150 | 0.545 | 19 | 0.400 | 14 | 4 | 5.5 | 755 x 485 x 495 | 125 |
| CL 7 | 10 | 150 | 0.728 | 25 | – | – | 5.5 | 7.5 | 755 x 485 x 495 | 130 |
| CL 7 | 13 | 190 | 0.525 | 19 | – | – | 5.5 | 7.5 | 755 x 485 x 495 | 130 |
| CL 7.5 | 10 | 150 | – | – | 0.680 | 24 | 5.5 | 7.5 | 755 x 485 x 495 | 130 |

CL series compressor system

| BOGE Type | Max. pressure | | Receiver capacity litres | Free air delivery* | | Free air delivery* | | Motor power | | Receiver option litres | Dimensions in mm W x D x H | Weight kg |
|-----------|---------------|------|--------------------------|--------------------|-----|--------------------|-----|-------------|-----|------------------------|-------------------------------|-----------|
| | bar | psig | | 50 Hz m³/min | cfm | 60 Hz m³/min | cfm | kW | HP | | | |
| CL 3 | 10 | 150 | 90 | 0.240 | 9 | – | – | 2.2 | 3 | 270 | 1130 x 490 x 920 | 155 |
| CL 4 | 10 | 150 | 90 | 0.340 | 12 | 0.310 | 11 | 3 | 4 | 270 | 1130 x 490 x 920 | 160 |
| CL 4 | 13 | 190 | 90 | 0.234 | 8 | – | – | 3 | 4 | 270 | 1130 x 490 x 920 | 165 |
| CL 5 | 10 | 150 | 90 | 0.545 | 19 | 0.400 | 14 | 4 | 5.5 | 270 | 1130 x 490 x 920 | 175 |
| CL 7 | 10 | 150 | 90 | 0.728 | 25 | – | – | 5.5 | 7.5 | 270 | 1130 x 490 x 920 | 180 |
| CL 7 | 13 | 190 | 90 | 0.525 | 19 | – | – | 5.5 | 7.5 | 270 | 1130 x 490 x 920 | 185 |
| CL 7.5 | 10 | 150 | 90 | – | – | 0.680 | 24 | 5.5 | 7.5 | 270 | 1130 x 490 x 920 | 180 |

CLD series compressed air centre

| BOGE Type | Max. pressure | | Receiver capacity litres | Free air delivery* | | Free air delivery* | | Motor power | | Dimensions in mm W x D x H | Weight kg |
|-----------|---------------|------|--------------------------|--------------------|-----|--------------------|-----|-------------|-----|-------------------------------|-----------|
| | bar | psig | | 50 Hz m³/min | cfm | 60 Hz m³/min | cfm | kW | HP | | |
| CLD 3 | 10 | 150 | 270 | 0.240 | 9 | – | – | 2.2 | 3 | 1715 x 545 x 1185 | 225 |
| CLD 4 | 10 | 150 | 270 | 0.340 | 12 | 0.310 | 11 | 3 | 4 | 1715 x 545 x 1185 | 230 |
| CLD 4 | 13 | 190 | 270 | 0.234 | 8 | – | – | 3 | 4 | 1715 x 545 x 1185 | 250 |
| CLD 5 | 10 | 150 | 270 | 0.545 | 19 | 0.400 | 14 | 4 | 5.5 | 1715 x 545 x 1185 | 245 |
| CLD 7 | 10 | 150 | 270 | 0.728 | 25 | – | – | 5.5 | 7.5 | 1715 x 545 x 1185 | 250 |
| CLD 7 | 13 | 190 | 270 | 0.525 | 19 | – | – | 5.5 | 7.5 | 1715 x 545 x 1185 | 270 |
| CLD 7.5 | 10 | 150 | 270 | – | – | 0.680 | 24 | 5.5 | 7.5 | 1715 x 545 x 1185 | 250 |

* Free air delivery for the complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.
Sound pressure level according to PN8NTC2.3 from **59 dB(A)**