



## Screw compressor duplex system S...DS

### 2 screw compressors mounted on the same receiver

BOGE Type	Receiver content litres	Max. pressure		Effective free air delivery*		Motor power	
		bar	psig	m <sup>3</sup> /min	cfm	kW	HP
S 10	750 D	8	115	2 x 1.18	2 x 42	2 x 7.5	2 x 10
		10	150	2 x 1.06	2 x 39	2 x 7.5	2 x 10
		13	190	2 x 0.91	2 x 32	2 x 7.5	2 x 10
S 15	750 D	8	115	2 x 1.65	2 x 58	2 x 11	2 x 15
		10	150	2 x 1.45	2 x 51	2 x 11	2 x 15
		13	190	2 x 1.25	2 x 44	2 x 11	2 x 15

BOGE Type	Dimensions in mm (W x D x H)	Weight kg
S 10-D...S 15-D	super-silenced from	2220 x 820 x 1750
	to	
S 10-D...S 15-D	ultra-silenced from	1650 x 790 x 1750
	to	
		325
		470
		340
		485

\* Free air delivery for complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.  
 Emitted sound level of each compressor as per PN8NTC2.3 from **66 dB(A)**.  
 Dimensions and construction details are subject to change.