



Compressor installation S Screw compressor receiver mounted

| BOGE Type | Receiver content litres | Max. pressure | | Effective free air delivery* | | Motor power | | Reiceiver option litres |
|--------------|-------------------------------|------------------|------|---------------------------------|-----|----------------|----|-------------------------------|
| | | bar | psig | m ³ /min | cfm | kW | HP | |
| S 10- | 270 | 8 | 115 | 1.18 | 42 | 7.5 | 10 | 350, 500, 750 |
| | | 10 | 150 | 1.06 | 39 | 7.5 | 10 | |
| | | 13 | 190 | 0.91 | 32 | 7.5 | 10 | |
| S 10- | 250 | 8 | 115 | 1.65 | 58 | 11 | 15 | 500, 750 |
| | | 10 | 150 | 1.45 | 51 | 11 | 15 | |
| | | 13 | 190 | 1.25 | 44 | 11 | 15 | |
| S 15- | 350 | 8 | 115 | 2.57 | 91 | 15 | 20 | |
| | | 10 | 150 | 2.24 | 80 | 15 | 20 | |
| | | 13 | 190 | 1.90 | 67 | 15 | 20 | |
| S 20-2- | 750 | 8 | 115 | 3.05 | 108 | 18.5 | 25 | |
| | | 10 | 150 | 2.66 | 94 | 18.5 | 25 | |
| | | 13 | 190 | 2.26 | 80 | 18.5 | 25 | |
| S 24-2- | 750 | 8 | 115 | 3.45 | 122 | 22 | 30 | |
| | | 10 | 150 | 3.11 | 110 | 22 | 30 | |
| | | 13 | 190 | 2.57 | 91 | 22 | 30 | |

| BOGE Type | Dimensions in mm (W x D x H) | Weight kg |
|---|------------------------------------|--------------|
| | | |
| S 10-...S 15- super-silenced from to ultra-silenced from to | 1650 x 790 x 1520 | 325 |
| | 2000 x 935 x 1760 | 470 |
| | 1650 x 790 x 1750 | 340 |
| | 2000 x 935 x 1990 | 485 |
| S 20-2-...S 29-2- super-silenced from to ultra-silenced from to | 2000 x 950 x 1950 | 600 |
| | 2000 x 950 x 1950 | 615 |
| | 2000 x 950 x 2300 | 625 |
| | 2000 x 950 x 2300 | 640 |

* Free air delivery for complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.
Emitted sound level of each compressor as per PN8NTC2.3 from **66 dB(A)**.
Dimensions and construction details are subject to change.