



Air compressor S Screw compressor

BOGE Type	Max. pressure		Effective free air delivery*		Motor power	
	bar	psig	m ³ /min	cfm	kW	HP
S 10	8	115	1.18	42	7.5	10
	10	150	1.06	39	7.5	10
	13	190	0.91	32	7.5	10
S 15	8	115	1.65	58	11	15
	10	150	1.45	51	11	15
	13	190	1.25	44	11	15
S 20-2	8	115	2.57	91	15	20
	10	150	2.24	80	15	20
	13	190	1.90	67	15	20
S 24-2	8	115	3.05	108	18.5	25
	10	150	2.66	94	18.5	25
	13	190	2.26	80	18.5	25
S 29-2	8	115	3.45	122	22	30
	10	150	3.11	110	22	30
	13	190	2.57	91	22	30

BOGE Type		Dimensions in mm (W x D x H)	Weight
			kg
S 10...S 15	super-silenced	940 x 700 x 970	220
	ultra-silenced	940 x 700 x 1200	235
S 20-2	super-silenced	1200 x 850 x 1150	350
	ultra-silenced	1200 x 850 x 1500	375
S 24-2...S 29-2	super-silenced	1200 x 850 x 1150	365
	ultra-silenced	1200 x 850 x 1500	390

* Free air delivery for complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.
Emitted sound level of each compressor as per PN8NTC2.3 from **66 dB(A)**.
Dimensions and construction details are subject to change.