



Compressor Centre SD / Screw compressor and refrigerant dryer receiver mounted

BOGE Type	Receiver content litres	Max. pressure		Effective free air delivery*		Motor power		Receiver option litres
		bar	psig	m ³ /min	cfm	kW	HP	
SD 10-	350	8	115	1.18	42	7.5	10	500, 750
		10	150	1.06	39	7.5	10	500, 750
		13	190	0.91	32	7.5	10	500, 750
SD 15-	350	8	115	1.65	58	11	15	500, 750
		10	150	1.45	51	11	15	500, 750
		13	190	1.25	44	11	15	500, 750
SD 20-2-	750	8	115	2.57	91	15	20	
		10	150	2.24	80	15	20	
		13	190	1.90	67	15	20	
SD 24-2-	750	8	115	3.05	108	18.5	25	
		10	150	2.66	94	18.5	25	
		13	190	2.26	80	18.5	25	
SD 29-2-	750	8	115	3.45	122	22	30	
		10	150	3.11	110	22	30	
		13	190	2.75	91	22	30	

BOGE Type	Dimensions in mm (W x D x H)	Weight kg
SD 10-...SD 15- super-silenced from to ultra-silenced from to	1650 x 790 x 1550	400
	2000 x 935 x 1760	520
	1650 x 790 x 1750	415
	2000 x 935 x 1990	535
SD 20-2-...SD 29-2- super-silenced from to ultra-silenced from to	2000 x 950 x 1950	670
	2000 x 950 x 1950	695
	2000 x 950 x 2300	695
	2000 x 950 x 2300	720

* Free air delivery for complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound level of each compressor as per PN8NTC2.3 from **66 dB(A)**. Dimensions and construction details are subject to change.

**incl. pressure loss air refrigerant dryer for SDF models.