



Compressor station SD / Screw compressor With integral refrigerant dryer

BOGE Type	Max. pressure**		Effective free air delivery*		Motor power	
	bar	psig	m ³ /min	cfm	kW	HP
SD 10	8	115	1.18	42	7.5	10
	10	150	1.06	39	7.5	10
	13	190	0.91	32	7.5	10
SD 15	8	115	1.65	58	11	15
	10	150	1.45	51	11	15
	13	190	1.25	44	11	15
SD 20-2	8	115	2.57	91	15	20
	10	150	2.24	80	15	20
	13	190	1.90	67	15	20
SD 24-2	8	115	3.05	108	18.5	25
	10	150	2.66	94	18.5	25
	13	190	2.26	80	18.5	25
SD 29-2	8	115	3.45	122	22	30
	10	150	3.11	110	22	30
	13	190	2.75	91	22	30

BOGE Type		Dimensions in mm	Weight
		(W x D x H)	kg
SD 10...SD 15	super-silenced	975 x 700 x 1265	260
	ultra-silenced	975 x 700 x 1495	275
SD 20-2	super-silenced	1200 x 850 x 1500	400
	ultra-silenced	1200 x 850 x 1850	425
SD 24-2...SD 29-2	super-silenced	1200 x 850 x 1500	425
	ultra-silenced	1200 x 850 x 1850	450

* Free air delivery for complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound level of each compressor as per PN8NTC2.3 from **66 dB(A)**. Dimensions and construction details are subject to change.

**incl. pressure loss air refrigerant dryer for SDF models.