

BOGE Type	Max. pressure**		Effective free air delivery*		Motor power				Dimensions silenced	Dimensions super-silenced	Compressed air outlet	Weight silenced kg	Weight super-silenced kg
	bar	psig	m ³ /min	cfm	Main drive motor kW	HP	Fan motor kW	HP	W x D x H (mm)	W x D x H (mm)			
SDF 60-2	8	115	1.75- 7.00	62-247	45	60	1.1	1.5	1620x 960x1665	1620x 960x1950	G 1 1/4	1005	1035
	10	150	1.58- 6.34	56-224	45	60	1.1	1.5	1620x 960x1665	1620x 960x1950	G 1 1/4	1005	1035
	13	190	1.34- 5.36	47-189	45	60	1.1	1.5	1620x 960x1665	1620x 960x1950	G 1 1/4	1005	1035
SDF 150	8	115	4.60-18.4	163-650	110	150	4.0	5.5	2365x1315x1755	2365x1315x2255	G 2 1/2	2400	2460
	10	150	4.08-16.3	144-575	110	150	4.0	5.5	2365x1315x1755	2365x1315x2255	G 2 1/2	2400	2460
	13	190	3.55-14.2	125-505	110	150	4.0	5.5	2365x1315x1755	2365x1315x2255	G 2 1/2	2400	2460

* Free air delivery for the complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.

** Max. compressor pressure

Emitted sound level as per PN8NTC2.3 from **71 dB(A)**.