

Screw compressor, frequency controlled and with integral refrigerant dryer



BOGE Type	Max. pressure**		Effective free air delivery*		Motor power		Dimensions in mm W x D x H	Weight kg
	bar	psig	m ³ /min	cfm	kW	HP		
SF 15-2	8	115	0.49-1.65	17- 58	11	15	940 x 700 x 1180	255
	10	150	0.39-1.45	14- 51	11	15	940 x 700 x 1180	255
	13	190	0.39-1.25	14- 44	11	15	940 x 700 x 1180	255
SF 24-2	8	115	0.85-3.05	30-108	18.5	25	1200 x 850 x 1403	337
	10	150	0.63-2.66	22- 94	18.5	25	1200 x 850 x 1403	337
	13	190	0.44-2.26	16- 80	18.5	25	1200 x 850 x 1403	337
SF 29-2	8	115	1.02-3.45	36-122	22	30	1200 x 850 x 1403	387
	10	150	0.88-3.11	31-110	22	30	1200 x 850 x 1403	387
	13	190	0.71-2.57	25- 91	22	30	1200 x 850 x 1403	387
SDF 15-2	8	115	0.49-1.65	17- 58	11	15	975 x 700 x 1470	295
	10	150	0.39-1.45	14- 51	11	15	975 x 700 x 1470	295
	13	190	0.39-1.25	14- 44	11	15	975 x 700 x 1470	295
SDF 24-2	8	115	0.85-3.05	30-108	18.5	25	1227 x 850 x 1750	450
	10	150	0.63-2.66	22- 94	18.5	25	1227 x 850 x 1750	450
	13	190	0.44-2.26	16- 80	18.5	25	1227 x 850 x 1750	450
SDF 29-2	8	115	1.02-3.45	36-122	22	30	1227 x 850 x 1750	450
	10	150	0.88-3.11	31-110	22	30	1227 x 850 x 1750	450
	13	190	0.71-2.57	25- 91	22	30	1227 x 850 x 1750	450

* Free air delivery for complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.

Emitted sound level of each compressor as per PN8NTC2.3 from **66 dB(A)**.

Dimensions and construction details are subject to change.

**incl. pressure loss air refrigerant dryer for SDF models.